



M+S

**DMO4**



Engineered primarily for off road conditions, the DMO4 is a drive-axle traction radial with deep, wide treads for high mobility. Powerful construction ensures durability and long life. Open shoulder offers agile maneuvering while large tread blocks and special compound resist cuts and penetrations. Rugged, four steel belt structure allows maximum load, provides fuel efficiency and high mileage.

M-Code	Size	PR	USE	Measuring Rim	Max. Air (PSI)		Max. Load				Overall Diameter		Section Width		Tread Width		Tread Depth		SLR
					S	D	(kgs)		(lbs)		mm	inch	mm	inch	mm	inch	mm	inch(32")	

**Tubeless**

3000140	11R22.5	148/145G	16		8.25	120	120	3000	2725	6610	6005	1075	42.3	282	11.1	220	8.7	24.7	31	498
3002014	11R22.5	148/145G	16	CE	8.25	120	120	3000	2725	6610	6005	1075	42.3	282	11.1	220	8.7	24.7	31	
3000920	11R24.5		16		8.25	120	120	3250	3000	7160	6610	1121	44.1	283	11.1	222	8.7	23.6	30	525
3002020	11R24.5		16	CE	8.25	120	120	3250	3000	7160	6610	1121	44.1	283	11.1	222	8.7	21.0	26	
3000142	12R22.5	152/148G	16		9.00	120	120	3350	3075	7390	6780	1102	43.4	300	11.8	235	9.3	25.0	31	515
3002045	12R22.5		16	P	9.00	120	120	3350	3075	7390	6780	1102	43.4	300	11.8	230	9.1	25.0	31	510
3000143	13R22.5	154/150G	18		9.75	120	120	3750	3450	8270	7610	1136	44.7	321	12.6	245	9.6	23.7	30	527
3001252	13R22.5	154/150G	18	CE	9.75	120	120	3750	3450	8270	7610	1136	44.7	321	12.6	245	9.6	24.0	30	527

**Tube Type**

3000135	1000R20	147/143G	16		7.50	120	120	3000	2725	6610	6005	1075	42.3	279	11.0	220	8.7	24.7	31	498
3000137	1100R20	150/146G	16		8.00	120	120	3350	3075	7390	6780	1102	43.4	294	11.6	235	9.3	25.0	31	515
3000138	1200R20	154/150G	18		8.50	120	120	3750	3450	8270	7610	1136	44.7	316	12.4	235	9.3	24.0	30	521
3000144	1200R24	156/153G	18		8.50	120	120	4250	3875	9370	8540	1231	48.5	319	12.6	245	9.6	20.9	26	572

Technical data subject to change without prior notice.

**Recommended Vehicle Types & Position**

