



ventus V2 concept



M-Code	Size	LI	SR	USE	PR	S/W Type	Recom- mended Rim	Max. Air (PSI)	Max.Load		Overall Diameter		Section Width		Tread Width		Tread Depth		SLR	RPM	Rolling Circum- ference
									(kgs)	(lbs)	mm	inch	mm	inch	mm	inch	mm	inch (32")			
65																					
1012901	175/65R14	82	H	CA	4	DSB	5.0	51	475	1047	583	23.0	180	7.1	130	5.1	8.0	10.1	905	1778	
1012814	185/65R14	86	H	CA	4	DSB	5.5	51	530	1168	595	23.4	187	7.4	137	5.4	8.0	10.1	887	1815	
60																					
1011711	185/60R13	80	H	-	4	DSB	5.5	51	450	992	553	21.8	187	7.4	136	5.4	7.6	9.5	954	1687	
1012812	185/60R14	82	H	CA	4	DSB	5.5	51	475	1047	574	22.6	194	7.6	137	5.4	8.0	10.1	919	1751	
1012813	195/60R14	86	H	CA	4	DSB	6.0	51	530	1168	589	23.2	204	8.0	144	5.7	8.0	10.1	896	1797	
1012815	195/60R15	88	H	CA	4	DSB	6.0	51	560	1235	614	24.2	204	8.0	146	5.7	8.0	10.1	859	1873	
1011712	195/55R15	85	V	-	4	DSB	6.0	51	515	1135	594	23.4	200	7.9	157	6.2	7.6	9.5	888	1812	
1011816	185/55R16	83	H	-	4	DSB	8.0	50	630	1389	637	25.1	225	8.9	190	7.5	7.8	9.7	828	1943	
1011714	205/55R16	91	H	-	4	DSB	7.0	51	615	1356	631	24.8	214	8.4	164	6.5	8.0	9.7	836	1925	
1011720	215/55R16	93	H	-	4	DSB	7.0	51	650	1433	642	25.3	223	8.8	171	6.7	7.8	9.7	822	1958	
55																					
1011721	225/55R16	95	H	-	4	DSB	7.0	51	690	1521	652	25.7	223	8.8	179	7.0	7.8	9.7	809	1989	
50																					
1011717	195/50R15	82	H	-	4	DSB	7.0	51	475	1047	646	25.4	229	9.0	171	6.7	7.6	9.5	817	1970	
1011718	205/50R15	86	H	-	4	DSB	7.0	51	530	1168	646	25.4	229	9.0	171	6.7	7.6	9.5	817	1970	
1011713	205/50R16	87	H	-	4	DSB	7.0	51	545	1201	612	24.1	212	8.3	164	6.5	7.8	9.7	862	1867	
1011715	225/50R16	92	V	-	4	DSB	7.0	51	630	1389	630	24.8	232	9.1	179	7.0	7.8	9.7	838	1922	
1011722	245/50R16	97	H	-	4	DSB	7.5	51	730	1609	650	25.6	262	10.3	196	7.7	7.8	9.7	812	1983	
1011725	205/50R17	XL 93	V	-	4	DSB	7.0	50	560	1235	615	24.2	206	8.1	172	6.8	7.8	9.7	858	1876	
1011716	215/50R17	91	V	-	4	DSB	7.0	51	615	1356	646	25.4	229	9.0	171	6.7	7.8	9.7	817	1970	
1011728	225/50R17	94	V	-	4	DSB	7.5	50	670	1477	651	25.6	225	8.9	190	7.5	7.8	9.7	811	1986	
45																					
1011719	205/45R16	83	H	-	4	DSB	7.0	51	487	1074	588	23.1	206	8.1	172	6.8	7.8	9.7	897	1793	
1012469	205/45R17	XL 88	V	-	4	DSB	7.0	50	560	1235	615	24.2	206	8.1	172	6.8	8.0	9.7	858	1876	
1012470	215/45R17	XL 91	V	-	4	DSB	7.0	50	615	1356	626	24.6	213	8.4	181	7.1	8.0	7.8	843	1909	
1012808	215/45R17	XL 91	V	CA	4	DSB	7.0	50	615	1356	623	24.5	221	8.7	181	7.1	8.2	7.8	847	1900	
1012471	225/45R17	XL 94	V	-	4	DSB	7.5	50	670	1477	651	25.6	206	8.1	190	7.5	8.0	9.8	811	1986	
1012809	225/45R17	XL 94	V	CA	4	DSB	7.5	50	670	1477	630	24.8	233	9.2	190	7.5	8.0	10.1	838	1922	
1012472	235/45R17	XL 97	V	-	4	DSB	8.0	50	730	1609	642	25.3	236	9.3	198	7.8	8.0	9.8	822	1958	
1012473	245/45R17	95	V	-	4	DSB	8.0	51	690	1521	651	25.6	245	9.6	206	8.1	8.0	9.8	811	1986	
1011731	215/45R18	XL 93	H	-	4	DSB	8.0	51	690	1521	651	25.6	245	9.6	206	8.1	7.8	9.7	811	1986	
1012465	225/45R18	XL 94	V	-	4	DSB	7.5	50	690	1521	659	25.9	225	8.9	190	7.5	8.0	9.8	801	2010	
40																					
1011723	205/40R17	XL 84	H	-	4	SBL	7.5	50	340	1102	596	23.5	212	8.3	172	6.8	8.0	9.8	885	1818	
1011732	225/40R18	XL 92	H	-	4	SBL	7.0	50	650	1433	651	25.6	212	8.3	181	7.1	7.8	9.7	811	1986	
1012464	235/40R18	XL 95	V	-	4	DSB	8.5	50	690	1521	645	25.4	241	9.5	197	7.8	8.0	9.8	818	1967	
35																					
1012463	265/35R18	93	V	-	4	DSB	9.5	51	650	1433	643	25.3	271	10.7	231	9.1	8.0	9.8	821	1961	

Technical data subject to change without prior notice. • These size are currently under development * XL : Extra Load
 * DSB : Diagonal Serrated Band * SBL : Serrated Black Letter

A Speed Revolution! You can enjoy a 'stable high-speed ride on a wet conditions' with the innovative technology exclusive to Hankook Tire. More Performance! The best 'stability of steering' and 'brake performance' that you can find. Realize the dream of driving.